

NAVIGATION LAMPS

P28s - E27 - Ba22d LONGLIFE 1500 Hrs




Fig. 7-1




Fig. 7-2




Fig. 7-3




Fig. 7-4




Fig. 7-5




Fig. 7-6

Article	Volt	Watt	Base	Ø	L-max.	A	CD	ISSA code	Fig.
289890100	24	40	P28s	38	108	46	50	73.228.01	7-1
289890200	28	40	P28s	38	108	46	50		7-1
289890300	110	60	P28s	38	108	46	50	73.228.03	7-2
289890400	110	80	P28s	38	108	46	70		7-2
289890500	220	65	P28s	38	108	46	50	73.228.04	7-2
289890700	220	85	P28s	38	108	46	70		7-2
279890100	24	40	E27	38	108	64	50	73.227.03	7-3
279890200	28	40	E27	38	108	64	50		7-3
279890300	110	60	E27	38	108	64	50	73.227.06	7-4
279890400	110	80	E27	38	108	64	70		7-4
279890500	220	65	E27	38	108	64	50	73.227.09	7-4
279890700	220	85	E27	38	108	64	70		7-4
229890100	24	40	Ba22d	38	108	58	50	73.226.06	7-5
229890200	28	40	Ba22d	38	108	58	50		7-5
229890300	110	60	Ba22d	38	108	58	50	73.226.11	7-6
229890400	110	80	Ba22d	38	108	58	70	73.226.12	7-6
229890500	220	65	Ba22d	38	108	58	50	73.226.16	7-6
229890700	220	85	Ba22d	38	108	58	70	73.226.17	7-6