

SAP Order No.: 136 4581

Product discription: 6200 0007 (L200N) is an Ag air- drying conductive lacquer (phthalate free) for a large number of application. It can be used in all cases where excellent electrically conductive layers are required (plastics, papers, wood, glasses, ceramics, metals, etc.)

Working conditions: The application of the paste is recommended as follows:

Redispersion: Please ensure that the paste is carefully homogenized before use. We recommend to use an electrical shaker or propeller stirrer at appr. 300 rpm for 10 min.

Thinner: This paste has a ready to use viscosity . If viscosity adjustment is necessary please use our thinner 6810 0222 .

Application: Paste can be applied by brush, spray gun or dipping.

Drying: 30 mins at 20 °C, Air or
10 mins at 80 °C, Air forced oven or
5 mins at 150°C , Air forced oven
Drying at any temperature up to 150 °C is possible.

Storage conditions: To avoid sedimentation of the solids and to prevent ageing of the paste we recommend storage conditions between 4 – 20 °C. If longer storage than 12 month is necessary we strongly recommend to store cool between 4 – 8 °C.

Product properties	Methods	Data
Silver content	At 800 °C, 10 minutes	45.0 ± 0.2 %
Viscosity	Flow cup - system, Din 53211 Ø 3mm at 25 °C	30 – 35 sec. Run out time
Resisitivity		10 - 40 mΩ /square; 10µm thicknesss

Ferro GmbH
Electronic Material Systems

Unsere Angaben über unsere Produkte und Geräte sowie über unsere Anlagen und Verfahren beruhen auf einer umfangreichen Forschungsarbeit und anwendungstechnischen Erfahrung. Wir vermitteln diese Ergebnisse , mit denen wir keine über den jeweiligen Einzelvertrag hinausgehende Haftung übernehmen, in Wort und Schrift nach bestem Wissen, behalten uns jedoch technische Änderungen im Zuge der Produktentwicklung vor. Das entbindet den Benutzer jedoch nicht davon, unsere Angaben und Empfehlungen vor ihrer Verwendung für den eigenen Gebrauch selbstverantwortlich zu prüfen. Das gilt besonders für Auslandslieferungen auch hinsichtlich der Wahrung von Schutzrechten Dritter, sowie für Anwendungen und Verfahrensweisen, die von uns nicht ausdrücklich schriftlich angegeben sind . Im Schadensfall beschränkt sich unserer Haftung auf Ersatzleistungen gleichen Umfangs, wie ssie unsere Allgemeinen Verkaufs- und Lieferbedingungen bei Qualitätsmängeln vorsehen.

DISCLAIMER: Reasonable care has been taken in the preparation of this information , but **FERRO EXTENDS NO WARRANTIES, MAKES NO REPRESENTATIONS AND ASSUMES NO RESPONSIBILITY AS TO ACCURACY OR SUITABILITY OF THIS INFORMATION OF THIS PRODUCT FOR ANY PURCHASER'S OR USER'S USE OR FOR ANY CONSEQUENCE OF ITS USE. FERRO DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR ANY PARTICULAR USE.** All statements, technical information and recommendations contained herein are based on Seller's or Manufacturer's test and the test of others, and are believed to be accurate, but no guarantee of accuracy is made. Judgment as to the suitability of information herein or the user's purposes are necessarily the user's responsibility. Users shall determine the suitability of the products for their own intended application.

Users assume all risk of use or handling whether or not in accordance with any statements or recommendation of the seller or manufacturer, Liability, if any, is and shall be limited to the replacement of such quantity of material proved not to conform to specifications as set out in product specification. Statements concerning the possible use of these products are not intended as recommendation to use these products in infringement of any patent. No guarantee is made that any use of the products does not infringe third-party intellectual property or patent rights anywhere in the world.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



62000007 Ag paste L200N

9562000007

specification 2063856
Version 1.0
material No. 1364581

Revision date 12.08.2009
Print Date 24.01.2011
Page 1 / 8

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

material No. : 1364581

Trade name : 9562000007
62000007 Ag paste L200N

Company : Ferro GmbH
Electronic Material Systems
Rodenbacher Chaussee 4
63457 Hanau

Telephone : +49 6181 59 3301
Telefax : +49 6181 59 3085

Emergency telephone : +49 (0)69 30 56 418
E-mail address : sdb@ferro.com

Use of the Substance/Preparation : Metallo-ceramic coating suited for firing, for the decoration of glass and ceramics.

2. HAZARDS IDENTIFICATION

Highly flammable.
Vapours may cause drowsiness and dizziness.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Product contains:
precious metal
glycol ether/-acetate
carbohydrate/(derivative of) cellulose
alcohol
aldehyde/ketone
carbonic acid/ester/anhydride

Information on ingredients/Hazardous components

• silver		Concentration	30% - 50%
CAS-No.	7440-22-4	EC-No.	231-131-3
• 1-ethoxypropan-2-ol		Concentration	20% - 30%
CAS-No.	52125-53-8, 1569-02-4	EC-No.	216-374-5
Symbol(s)		R-phrased(s)	R10, R67
• ethanol		Concentration	12,5% - 20%
CAS-No.	64-17-5	EC-No.	200-578-6
Symbol(s)	F	R-phrased(s)	R11
• acetone		Concentration	5% - 7%
CAS-No.	67-64-1	EC-No.	200-662-2
Symbol(s)	F, Xi	R-phrased(s)	R11, R36, R66, R67

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

62000007 Ag paste L200N

9562000007

specification 2063856

Revision date

12.08.2009

Version 1.0

Print Date

24.01.2011

material No. 1364581

Page

2 / 8

• ethyl acetate

CAS-No. 141-78-6

Symbol(s) F, Xi

Concentration

1% - 3%

EC-No.

205-500-4

R-phrases(s)

R11, R36, R66, R67

See chapter 16 for text of risk phrases

4. FIRST AID MEASURES

General advice

Bring affected person out of danger area. Place person on side in stable position if unconscious. Employ mouth-to-mouth resuscitation if breathing ceases. Remove contaminated or saturated clothing.

Inhalation

Take affected persons out into the fresh air.

Skin contact

Wash off immediately with soap and plenty of water. Remove contaminated or saturated clothing.

Eye contact

Immediately flush eye(s) with plenty of water.

Ingestion

Have patient drink plenty of water in small sips.

Notes to physician

No own experience available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water (spray jet), mist, special quenching powder, quenching foam (use large amount of foam as it will be partially destroyed), carbon dioxide.

Extinguishing media which shall not be used for safety reasons

High volume water jet

Specific hazards during fire fighting

When heated, formation of explosive vapour/air mixtures. May be released in case of fire: flammable smouldering gases.

Special protective equipment for fire-fighters

Employ protective equipment commonly used in the event of fire.

Further information

In case of fire, remove the endangered containers and bring to a safe place, if this can be done safely.

Water used to extinguish fire should not enter drainage systems, soil, or stretches of water. Ensure there are sufficient retaining facilities for water used to extinguish fire. Contaminated fire-extinguishing water must be disposed of in accordance with the regulations issued by the appropriate local authorities.

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

62000007 Ag paste L200N

9562000007

specification 2063856

Revision date

12.08.2009

Version 1.0

Print Date

24.01.2011

material No. 1364581

Page

3 / 8

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Ensure adequate ventilation.

Remove all sources of ignition.

Wear personal protective equipment; see section 8.

Environmental precautions

Avoid penetration into drainage system or in rooms situated at a lower level because of danger of explosion.

Prevent penetration into soil, stretches of water and drainage systems.

Methods for cleaning up

Absorb with liquid-binding material (e.g. inert absorbent kieselguhruniversal binder) pick up.

Additional advice

Dispose of contaminated material as waste in accordance with section 13.

7. HANDLING AND STORAGE

Handling

Safe handling advice

Do not breathe in vapours or aerosols.

Keep away from sources of ignition - No smoking.

Advice on protection against fire and explosion

Take measures to prevent the build up of electrostatic charge.

Highly volatile substances may be released during processing; therefore avoid sources of ignition.

Storage

Requirements for storage areas and containers

Fumes may be released in closed storage rooms or during processing. Store in a dry place at room temperature.

Store in cool place.

Further information

Product is slightly water-pollutive. Observe the national and local regulations concerning handling and storage.

Advice on common storage

No materials to be especially mentioned.

German storage class

3 A (Classification by producer in accordance with VCI scheme)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

• silver

CAS-No.

7440-22-4

EC-No.

231-131-3

Control parameters

0,10 mg/m³
(total dust)

AGW (Germany)

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

62000007 Ag paste L200N

9562000007

specification	2063856	Revision date	12.08.2009
Version	1.0	Print Date	24.01.2011
material No.	1364581	Page	4 / 8

• 1-ethoxypropan-2-ol

CAS-No. 52125-53-8, 1569-02-4 EC-No. 216-374-5
50,00 ml/m³
220,00 mg/m³
remarks: H
AGW (Germany)

• ethanol

CAS-No. 64-17-5 EC-No. 200-578-6
500,00 ml/m³
960,00 mg/m³
AGW (Germany)

• acetone

CAS-No. 67-64-1 EC-No. 200-662-2
500,00 ml/m³
1.200,00 mg/m³
AGW (Germany)

• ethyl acetate

CAS-No. 141-78-6 EC-No. 205-500-4
400,00 ml/m³
1.500,00 mg/m³
AGW (Germany)

Engineering measures

If possible, use material transfer/filling, metering and blending plants that are closed.
Take precautionary measures against static discharges. Earthing of equipment.
Eventual aspiration in case of solvent fumes. Technical protection measures have always priority over personal protection equipment.

Occupational exposure controls

Personal protective equipment

Respiratory protection

Ensure suitable suction/aeration at the work place and with operational machinery.

If workplace exposure limit is exceeded apply Respirator with brown A-type filter.

Hand protection

Wear protective gloves made of the following materials: nitrile rubber.

Eye protection

wear basket-shaped glasses or safety goggles with side-shields.

Skin and body protection

When handling larger quantities: rubber apron, plastic apron.

Safety shoes

Hygiene measures

Wash hands before breaks and at the end of workday.

Protective measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

62000007 Ag paste L200N

9562000007

specification 2063856

Revision date

12.08.2009

Version 1.0

Print Date

24.01.2011

material No. 1364581

Page

5 / 8

Colour silver
Odour characteristic

Safety data

physical state liquid

Flash point 12 °C DIN 51755 Part 1

Lower explosion limit 1,3 %(V)

Upper explosion limit 19 %(V)

Vapour pressure > 1.100 - 1.750 hPa (50 °C)

Density 1,44 g/cm³ (20 °C)

Water solubility soluble

10. STABILITY AND REACTIVITY

Conditions to avoid No dangerous reaction known under conditions of normal use.

Materials to avoid Strong oxidizing agents

Hazardous decomposition products none known

11. TOXICOLOGICAL INFORMATION

Skin irritation not known

Eye irritation Vapour during processing may be irritating to the respiratory tract and to the eyes.

Sensitisation not known

No results of animal experiments with the product available.

Acute oral toxicity

ethanol LD50 rat: 6.200,00 mg/kg

acetone LD50 rat: 5.800,00 mg/kg

ethyl acetate LD50 rat: 5.620,00 mg/kg

Acute inhalation toxicity

ethanol LC50 rat: > 8.000,00 mg/l / 4 h

acetone LC50 rat: 76,00 mg/l / 4 h

ethyl acetate LC50 rat: 1.600,00 mg/l / 8 h

Acute dermal toxicity

ethanol LD50 rabbit: > 20.000,00 mg/kg

acetone LD50 rabbit: 20.000,00 mg/kg

ethyl acetate LD50 rabbit: > 18.000,00 mg/kg

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

62000007 Ag paste L200N

9562000007

specification 2063856

Revision date

12.08.2009

Version 1.0

Print Date

24.01.2011

material No. 1364581

Page

6 / 8

12. ECOLOGICAL INFORMATION

Persistence and degradability

Biodegradability no data available

Physico-chemical removability no data available

Ecotoxicity effects

Specific information for this product is not available.

Toxicity to fish

ethanol LC50 Fish: 8.140,00 mg/l / 48 h

acetone LC50 Fish: 8.300,00 mg/l / 96 h

ethyl acetate LC50 Fish: 270,00 mg/l

Toxicity to daphnia

ethanol EC50 Daphnia: > 9.268,00 mg/l / 48 h

acetone EC50 Daphnia: 12.600,00 mg/l / 48 h

ethyl acetate EC50 Daphnia: 2.306,00 mg/l / 24 h

13. DISPOSAL CONSIDERATIONS

Product

Do not contaminate ponds, waterways or ditches with chemical or used container.

In agreement with the waste code must be determined regional waste disposal authority or company.

Dispose of as special waste in compliance with local and national regulations.

Do not dispose of waste into sewer.

Uncleaned packaging

If there is product residue in the emptied container, follow directions for handling on the container's label.

Dispose of as unused product.

14. TRANSPORT INFORMATION

Land transport ADR/RID/GGVSE (Germany)

Class 3
Code F1
Packaging group II
orange warning plate 33 / 1263
Description of the goods (Technical name)
1263 PAINT (SP 640C)

Sea transport IMDG-Code/GGVSee

Class 3
UN-Number 1263
Packaging group II
Proper technical name (Proper shipping name)
PAINT

Air transport ICAO-TI/IATA-DGR

Class 3
UN-Number 1263

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

62000007 Ag paste L200N

9562000007

specification 2063856

Revision date

12.08.2009

Version 1.0

Print Date

24.01.2011

material No. 1364581

Page

7 / 8

Packaging group II
Proper technical name (Proper shipping name)
Paint

15. REGULATORY INFORMATION

Labelling according to EC Directives

statutory basis/list 1999/45/EC

Symbol(s) F Highly flammable

R-phrases(s) R11 Highly flammable.
R67 Vapours may cause drowsiness and dizziness.

S-phrases(s) S 9 Keep container in a well-ventilated place.
S16 Keep away from sources of ignition - No smoking.
S33 Take precautionary measures against static discharges.
S60 This material and its container must be disposed of as hazardous waste.

Major Accident Hazard Legislation 96/82/EC listing: Update: 2003
Highly flammable (7b)

National legislation (Germany)

Water contaminating class (Germany) WGK 1 slightly water endangering
Update: VWWWS A4

TA Luft List (Germany)	Class	I	II	III	IV
	organic	0,0 %	0,0 %	0,0 %	
	carcinogenic	0,0 %	0,0 %	0,0 %	
	inorganic-dust-like	0,0 %	0,0 %	0,0 %	
	inorganic-gaseous	0,0 %	0,0 %	0,0 %	0,0 %

Other regulations The employment limitations under the regulations to the protection from hazardous materials of pregnant women and young mothers guideline and the protection of young persons act are to be observed.

16. OTHER INFORMATION

Risk phrase (R phrase) texts

• 1-ethoxypropan-2-ol

R10 Flammable.
R67 Vapours may cause drowsiness and dizziness.

• ethanol

R11 Highly flammable.

• acetone

R11 Highly flammable.
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

62000007 Ag paste L200N

9562000007

specification	2063856	Revision date	12.08.2009
Version	1.0	Print Date	24.01.2011
material No.	1364581	Page	8 / 8

- R67 Vapours may cause drowsiness and dizziness.
- **ethyl acetate**
 - R11 Highly flammable.
 - R36 Irritating to eyes.
 - R66 Repeated exposure may cause skin dryness or cracking.
 - R67 Vapours may cause drowsiness and dizziness.

Further information

Data sheet producing department:
Ferro US-PS Telephone: +49 (0)69 27116-605

Changes since the last version will be highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.